



## OZZ XR3 P9" 65 Arctic Edition Driving light LED

The OZZ XR3 P9" 65 retains the powerful specifications of previous models XR2 P9" and XR3 P9" but also feature a powerful E-approved amber warning light, adding a layer of functionality for professional and safety-conscious drivers. The boost function of this driving light provides an intense 10,424 lumens, achieving 1 lux at up to 735 meters, making it ideal for long-range visibility on dark roads or challenging off-road adventures. It's also equipped with OZZ's signature dual dynamic position light in white and amber. With a color temperature of 5000 K, the XR3 P9" 65 emits a clear, powerful light that enhances visibility even in the darkest of

<b>Art. no.</b>	88108	<b>Color LED</b>	White, amber
<b>Pcs LED</b>	16	<b>Connection</b>	6-pin DT male + female
<b>Voltage</b>	10-35V DC	<b>Cable lenght (mm)</b>	1000 (800+200)
<b>Theoretical effect</b>	160W	<b>Material bracket</b>	Stainless steel
<b>Actual effect</b>	R112: 74W, boost: 130W (12V DC), R112: 73W, boost: 135W (24V DC)	<b>Material housing</b>	Aluminum
<b>Nominal current</b>	R112: 6,14A, boost: 11,17A (12V DC), R112: 3,04A, boost: 5,62A (24V DC)	<b>Material lens</b>	Polycarbonate
<b>Functions</b>	High beam, Boost mode, Dynamic position light, Warning light	<b>Lenght (mm)</b>	220
<b>Theoretical lumen</b>	15000	<b>Depth (mm)</b>	84,3
<b>Actual lumen</b>	R112: 7010, Boost: 10424	<b>Height (mm)</b>	210
<b>1 lux @</b>	R112: 480 m, Boost: 735 m	<b>Height including bracket (mm)</b>	227
<b>Kelvin</b>	5000K	<b>Diameter (mm)</b>	220
<b>IP-class</b>	IP68/IP69K	<b>CC (mm)</b>	-
<b>Beam pattern</b>	Driving	<b>Operating temperature</b>	-40°C - +60°C
<b>Flash light pattern</b>	Double flash	<b>E-mark approval</b>	ECE R148, R149, R65
<b>Position light</b>	Dynamic white and amber	<b>Reference number</b>	50
<b>Color housing</b>	White	<b>EMC</b>	ECE R10
<b>RAL color</b>	RAL9003	<b>Pcs in master box</b>	4
<b>Color lens</b>	Clear	<b>EAN</b>	7350166880170
		<b>Warranty</b>	3 years

