

OZZ XH1

Introducing OZZ XH1 – a headlight/snowplow lamp that redefines versatility. Emitting 1700 lumens in low beam and an impressive 3100 lumens in high beam, it's your go-to solution on the road. The automatic heated lens ensures clarity in all conditions, and with a 1 lux reach of 183 meters (low beam) and 365 meters (high beam), visibility is unmatched. OZZ XH1 seamlessly blends functionality with style, providing a natural 5000 K light. OZZ XH1 offers indicator and dual position light as well as universal mounting on either side of your vehicle. The side unit is easily adjustable based on your installation, thanks to its flexible and detachable design.

		1			
Art. no.	88301				
Lamp type	LED	-		-	
Diodes	49 pcs	-		-	-
Voltage	10-30V DC	1 F			_
Actual effect 12V	High beam: 48W, low beam: 22.8W, indicator: 12W, position light: 2.4W, heater: 30W				
Actual effect 24V	Hight beam: 48W, low beam: 24W, indicator: 12W, position light: 2.4W, heater: 21.6W	F F			
Nominal current at 12 V	High beam: 4A, low beam: 1.9A, indicator: 1A, position light: 0.2A, heater: 2.5A	. L			
Nominal current at 24 V	Hight beam: 2.0A, low beam: 1.0A, indicator: 0.5A, position light: 0.1A, heater: 0.9A				
Theoretical lumen (Lm)	Low beam: 2400, high beam: 4500				
Actual lumen	Low beam: 1700, high beam: 3100	matrice (m			
1 lux @	High beam: 365m, low beam: 183m	metres (n	1)		
Kelvin (K)	5000	30 — —			
IP-class	IP68/IP69K	15			
Beam pattern	driving	•	2054)10
Position light	white and amber	15 -			
Connection	6-pin DT	30		\sim	
Material chassi, lens	aluminum, hardened glass	0	25		58
Lenght, depth, height (mm)	224,5, 80, 150	, U	25		56
Operating temperature	-40 - +60°C	30		+	+
E-mark approval	R148 (R7, R6), R149 (R112)	15			
EMC	ECE R10				
Ref. no.	27,5	0	218-	10	-1Lux
Weight (kg)	1,75	15		+	+
Warranty	3 years	30			
		0	25	116	369



1Lux

183